

PTC-PR2 Queuing system-ticket machine (Standalone)

PTC-PR2 TICKET MACHINE (No sounds)	
PRINT	User's logo / advertisement / date / time / numbers Ticket print time within 2 seconds
PRINT TICKET	Push the button to get a ticket
DISPLAY	2 digits number (0~99) Standalone: Shows daily ticket taken number
CONTROL IC	With control IC, do not need to be controlled by PC or other equipment
MEMORY	When power outage, every request was in storage
BEEP REMIND	Paper out or error
DIMENSIONS	L 24.5cm W 14.5cm H 24.5cm Weight 2.12 KG
PAPER	80mm * 80m continuous thermal paper Min. ticket length 5cm
POWER	AV100~240V



PTC-PR2 Queuing system-ticket machine (Online)

PTC-PR2 TICKET MACHINE (Dingdong or Speech Sounds)	
PRINT	User's logo / advertisement / date / time / numbers Ticket print time within 2 seconds
PRINT TICKET	Push the button to get a ticket
DISPLAY	2 digits number (0~99) Online: Shows waiting number
CONTROL IC	With control IC, do not need to be controlled by PC or other equipment Waiting number can be automatically counted and changed
MEMORY	When power outage, every request was in storage
COUNTERS	Max. 8 counters
Sounds	Ding-dong or Speech Sounds Volume adjustable Speech sounds only Chinese available
DIMENSIONS	L 24.5cm W 14.5cm H 24.5cm Weight 2.2 KG
PAPER	80mm * 80m continuous thermal paper Min. ticket length 5cm
POWER	AV100~240V



Short Display & keyboard

Dimensions	Display	L 35cm W 13.5cm H 5cm Weight 1.67 KG
	Keyboard	L 14cm W 10cm H 2.5cm Weight 0.4 KG
Power	One power supply by RS-485 connect cable Input: Power adapter 110V – 240V AC Output: 12VDC / 1A	
Display	Interface	RS-485 long distance transfer No data missing
	Function	Ultra bright seven-segment display 3 digits (0 – 999)
	Indicator	1.[DingDong] indicator. Volume can be adjusted. 2.Turn off [DingDong] indicator ◦
Keyboard	Interface	RS-485 long distance transfer No data missing
	Ultra bright seven-segment display 3 digits (0 – 999)	
	To call the next customer	Press [CALL]
	To call the specific number	Enter the number 0-9 and press [CALL]
	Recall	Press [RECALL]
	Voice Indicator	Turn on or turn off [DingDong] indicator of the display

A custom-made order is acceptable



Big Display

Dimensions	Display	L 105cm W 18cm H 5cm
	Weight	5.5 Kg
Power	One power supply by RS-485 connect cable	
Display	Interface	RS-485 long distance transfer No data missing
	Function	Ultra bright seven-segment display Left: 3 digits (0 – 999) Right: 2 digits (0 – 99)
	Indicator	1.[DingDong] indicator. Volume can be adjusted. 2.Turn off [DingDong] indicator ◦

A custom-made order is acceptable

